


BRONZE CLOSE COUPLED ROTARY GEAR PUMPS

GEAR PUMPS SERIES N992

PERFORMANCE



FEATURES


- Rugged Corrosion Resistant Bronze Construction
- Compact Close-Coupled Design
- Stainless Steel Shafts
- Durable Bronze Helical Gears Provide Quiet Operation
- Process Lubricated Carbon Graphite Bearings
- O-Ring Cover Seal For Maximum Leak Protection
- Lip Seal or Mechanical Seal

Easy Field Assembly to a Variety of Motor Frames - For Typical DC Motor Pump Units - see N992 DC

- For Compact AC Motor Pump Units see Close Coupled Bronze Adapterless Rotary Gear Pumps - For Danfoss Hydraulic Motor Driven Pump Units - See Adapter 9960 For Bronze Pedestal Pumps - See Model N2000 For Close-Coupled Ductile Iron Pumps - See Model C992

LIQUIDS AND TEMPERATURE




These pumps are suitable for all liquids that are compatible with bronze. Most common liquids are water, oil, and mild chemicals in the pH range of 4 to 11. Viscous liquids require reduced shaft speeds of 1150 RPM or lower. (Consult factory.) Liquids containing solids, abrasives, powders, or paint pigments are definitely not recommended for gear pumps. If abrasives are unavoidable, use a very low shaft speed. See price book for the recommended liquid temperature range of lip and mechanical seals. If more extreme temperature conditions exist, factory should be consulted. Freezing of water-filled pumps can cause damage and must be avoided. Oils at low temperatures are very viscous requiring a lower speed or extra power.



SUCTION LIFT

As a general rule, the suction lift should be kept at an absolute minimum by placing the pump as close to the liquid source as possible. A gear pump in new condition can lift 20 feet of water in the suction line. A foot valve (preferably with built-in strainer) is recommended at the beginning of the suction line. For a first startup, the pump should be primed to avoid dry running. Minimum size of the suction pipe is the size of the pump inlet port. For longer suction lines (over 3 feet) or for viscous liquids, the pipe should be at least one size or two sizes larger than the pump inlet port. If the discharge line contains any throttling devices such as a shut-off valve, a spray nozzle or other restrictive device, it is necessary to have a relief valve in the system, which returns the liquid to the suction side or to the tank. The relief valve is also available as part of the pump itself (R-model pumps). However, built-in relief valves are only good for intermittent service. If used continuously, the pump will overheat. A built-in relief valve is strictly a safety device against overpressure. It will not work successfully as a pressure or flow control device. For this purpose a separate relief valve in the pressure line must be used. Unless otherwise specified, the pump motor unit is supplied by the factory for shaft rotation counterclockwise from shaft end. Reversing motor will reverse "in and "out" ports and also requires changing relief valve location. The relief valve is always on the inlet side of this pump series. The factory pressure setting is 50 PSIG. To increase pressure, turn the relief valve adjusting screw in a clockwise direction.

EXPLODED VIEW AND PARTS LIST



N992 & N992S5

N992R & N992RS5

N992S16 & N992S17


N992RS16 & N992RS17



	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24				
	Screw	Body	Bearing	Drive Gear Assy	Idle Gear Assy	Dowel Pin	O-Ring	Cover	Tag	Tag Screw	Screw	Lipseal	Mechanical Seal	Coupling Half	Retaining Ring	Retaining Ring	Ball	Spring	O-Ring	O-Ring	Nut Plug	Adjust. Screw	Lock Nut	Nut Bypass	Lock Ring	Repair Kits		
Pump No.	Qty. 6	Qty. 1	Qty. 4	Qty. 1	Qty. 1	Qty. 2	Qty. 1	Qty. 1	Qty. 1	Qty. 2	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 2	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1			
N992	7733	9306NC5N	5024	32994	32993	8885	9797-038	9308NN2N	9344	9345	5595	5007	N/A	5604	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10631	
N992R	7733	9306NC5N	5024	32994	32993	8885	9797-038	9308NN3B	9344	9345	5595	5007	N/A	5604	N/A	N/A	5803	1840	9797-019	9797-015	1838	5237	5240D	5239	N/A			
N992S5	7733	9306NC5N	5024	32994	32993	8885	9797-038	9308NN2N	9344	9345	5595	7580	N/A	5604	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7626		
N992RS5	7733	9306NC5N	5024	32994	32993	8885	9797-038	9308NN3B	9344	9345	5595	7580	N/A	5604	N/A	N/A	5803	1840	9797-019	9797-015	1838	5237	5240D	5239	7626	11351		
N992S16	7733	9306NC5N	5024	33341	32993	8885	9797-038	9309PN4N	9344	9345	5595	N/A	32584	5604	5373	7639	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		N/A	
N992RS16	7733	9306NC5N	5024	33341	32993	8885	9797-038	9309PN4B	9344	9345	5595	N/A	32584	5604	5373	7639	5803	6302	9797-019	9797-015	1838	5237	5240D	5239	N/A		12396	
N992S17	7733	9306NC5N	5024	33341	32993	8885	9797-038	9309PN4N	9344	9345	5595	N/A	32585	5604	5373	7639	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	12397	
N992RS17	7733	9306NC5N	5024	33341	32993	8885	9797-038	9309PN4B	9344	9345	5595	N/A	32585	5604	5373	7639	5803	6302	9797-019	9797-015	1838	5237	5240D	5239	N/A			

Adapter Kits

Adapter Kit	Part Number	Description
M	10562	48 Frame
N	10816	56 Frame
P	11722	S56 Frame
Q	11331	56C Frame (to 3/4 HP)
C	11331H	56C Frame (above 3/4 HP)
F	11332	IEC71
N/A	N/A	Adapterless - Modified 48

DIMENSIONS







Bronze Close Coupled Rotary Gear Pumps
N992 Series



Bronze Close Coupled
Rotary Gear Pumps
N992 Series

Dimensions



NBR = Acrylonitrile-Butadiene PTFE = Polytetrafluorethylene FKM = Fluoroelastomer



5900 Firestone Drive, Syracuse, NY 13206
Phone: (800) 448-1668; (315) 437-0361 • Fax: (315) 463-9561

Visit www.oberdorferpumps.com to find in-depth descriptions of the world's leading high-quality, dependable pumps.
Due to ongoing product improvements, data shown here is subject to change without notice. Contact Oberdorfer Pumps for latest specifications.

3/8" NPT Ports Standard





Table with 2 columns: Pump, Description. Rows list various pump models and their features like standard pump, relief valve, lipseal, mechanical seal, etc.

FEATURES:

- Rugged corrosion resistant bronze construction
- Compact close-coupled design
- Stainless steel shafts
- Durable bronze helical gears provide quiet operation
- Process lubricated carbon graphite bearings
- O-ring cover seal for maximum leak protection
- Shaft seal choices: Lip & Mechanical
- Easy field assembly to a variety of motor frames
- For typical DC motor pump units see N992 DC
- For compact AC motor pump units see Close Coupled Bronze Adapterless Rotary Gear Pumps
- For Danfoss hydraulic motor driven pump units see adapter 9960
- For bronze pedestal pumps - see model N2000
- For close-coupled ductile iron pumps - see model C992

PERFORMANCE:

Capacity Water at 70° F



GENERAL DESCRIPTION:

Pump housings and gears are made of top quality bronze, shafts are 303 stainless steel. Bearings are designed of high performance carbongraphite material selected for wear resistance and long service life. Gear pumps are positive displacement pumps. Each shaft revolution displaces a definite amount of liquid relatively unaffected by the back pressure in the discharge line. Shaft speed and flow are directly proportional. Recommended pressure limits are 100 PSI for water and non-lubricants, 150 PSI for oil and other lubricants. The maximum shaft speed is 1750 RPM.

SHAFT SEALS:

Close coupled gear pumps are normally supplied with a NBR lip seal. A lip seal made of FKM is available as an option. For a FKM Seal, add S5 to the pump model number. For NBR mechanical add S16. For FKM mechanical add S17. For PTFE mechanical add S18. For EPDM mechanical add S8.

LIQUIDS AND TEMPERATURE:

These pumps are suitable for all liquids that are compatible with bronze. Most common liquids are water, oil, and mild chemicals in the pH range of 4 to 11. Viscous liquids require reduced shaft speeds of 1140 RPM or lower. (Consult factory.)

Liquids containing solids, abrasives, powders, or paint pigments are definitely not recommended for gear pumps. If abrasives are unavoidable, use a very low shaft speed. The recommended liquid temperature range is from 32° F to 140° F for best pump life. If more extreme

Bronze Close Coupled Rotary Gear Pumps
N992 Series

temperature conditions exist, factory should be consulted. Freezing of water-filled pumps can cause damage and must be avoided. Oils at low temperatures are very vis-
cous requiring a lower speed or extra power.

SUCTION LIFT:
As a general rule, the suction lift should be kept at an absolute minimum by placing the pump as close to the liquid source as possible. A gear pump in new condition can lift 20 feet of water in the suction line. A foot valve (preferably with built-in strainer) is recommended at the beginning of the suction line. For a first start-up, the pump should be primed to avoid dry running. Minimum size of the suction pipe is the size of the pump inlet port. For longer suction lines (over 3 feet) or for viscous liquids, the pipe should be at least one size or two sizes larger than the pump inlet port.

ROTATION AND RELIEF VALVE:
If the discharge line contains any throttling devices such as a shut-off valve, a spray nozzle or other restrictive device, it is necessary to have a relief valve in the system which returns the liquid to the suction side or to the tank. The relief valve is also available as part of the pump itself (R-model pumps). However, built-in relief valves are only good for intermittent service. If used continuously,

the pump will overheat. A built-in relief valve is strictly a safety device against overpressure. It will not work successfully as a pressure or flow control device. For this purpose a separate relief valve in the pressure line must be used. Unless otherwise specified, the pump motor unit is supplied by the factory for shaft rotation counterclock-
wise from pump shaft end. Reversing motor will reverse “in and “out” ports and also requires changing relief valve location. The relief valve is always on the inlet side of this pump series. The factory pressure setting is 50 PSIG. To increase pressure, turn the relief valve adjust-
ing screw in a clockwise direction.

Table with 3 columns: Adapter Kit, Part Number, Description. Rows include M (48 Frame), N (56 Frame), P (S56 Frame), Q (56C Frame), C (56C Frame), F (IEC71), and N/A (Adapterless).

Parts List

Table with 14 columns: 1 (Screw), 2 (Body), 3 (Bearing), 4 (Drive Gear Assy), 5 (Idle Gear Assy), 6 (Dowel Pin), 7 (O-Ring), 8 (Cover), 9 (Tag), 10 (Tag Screw), 11 (Screw), 12 (Lipseal), 13 (Mechanical Seal). Rows list various pump models and their corresponding part numbers.

Repair Kits contain items 3, 4, 5, 7 12, 14, 15, 24

Exploded View




Table with 16 columns: 13 (Coupling Half), 14 (Retaining Ring), 15 (Retaining Ring), 16 (Poppet or Ball), 17 (Spring), 18 (O-Ring), 19 (O-Ring), 20 (Nut Plug), 21 (Adjust. Screw), 22 (Lock Nut), 23 (Nut Bypass), 24 (Lock Ring), 25 (Pipe Plug), and Repair Kits. Rows list various pump models and their corresponding part numbers.