

# MARINE PRODUCT DATA SHEET

**DEM:** 330-010 (3/4" FITTING) **AFTERMARKET:** 330-021 (Both FITTINGS)

Keep your bait alive. The SHURflo Livewell Fill Valve creates an energized environment that "keeps your bait alive." The full port fittings (3/4" or 1-1/8") assure the amount of flow is achieve and maintained. The adjustable flow valve allows you to adjust the water flow to your desire amount.

# **TYPICAL APPLICATIONS**

Livewell tank water circulation

## **MATERIAL**

Plastics: Nylon
Flow Adjustment: Santoprene
Gasket: Buna

Screws Stainless Steel

### **SPECIFICATIONS**

Inlet Port: 3/4" Barb

Liquid temperature: 130°F [24°C] Max


Max Pressure: 15 PSI


#### **WARRANTY**

3 Year Limited Warranty See SB-1050 for Warranty Details

# **RELATED DOCUMENTS**

Catalog: MS-030-140
Installation Manual: 911-734
Maintenance: 911-734
Applications Spec Guide: MS-020-005
Warranty: SB-1050





SHURflo reserves the right to update specifications, prices, or make substitutions.



#### **SHURflo, LLC Headquarters**

5900 Katella Avenue Cypress, California 90630 Phone (562) 795-5200 • Toll Free (800) 854-3218 Fax (562) 795-7564

#### SHURflo, LLC East

52748 Park Six Court Elkhart, Indiana 46514-5427 Phone (562) 795-5200 • Toll Free (800) 854-3218 Fax (574) 264-2169

## SHURflo Europe, Middle East, Africa Pentair Water Belgium bvba,

Industriepark Wolfstee, Toekomstlaan 30 B-2200 Herentals, Belgium Phone +32-14-283500• Fax +32-14-283505